


Refs.
D2409
DIN 338

HSS drill with carbide tip

NEW



Features
carbide tip,
sharped with
diamond wheel,
tolerance measures,
angle point,
Helix type

Benefits
Drilling of the steels
until 2100N/mm2

Materials
Refractory steel, cast,
stainless steel, copper,
composite materials

Complete range: diameter every 0.10 mm, consult our INDUSTRY CATALOGUE

Ø	WL TL	ref.	EAN	packaging*
1,50	18 40	D2409D0150	3336600121287	x1
2	24 49	D2409D0200	3336600121331	x1
2,50	30 57	D2409D0250	3336600121386	x1
2,80	33 61	D2409D0280	3336600121416	x1
3	33 61	D2409D0300	3336600121430	x1
3,20	36 65	D2409D0320	3336600121454	x1
3,30	36 65	D2409D0330	3336600121461	x1
3,50	39 70	D2409D0350	3336600121485	x1
4	43 75	D2409D0400	3336600121539	x1
4,20	43 75	D2409D0420	3336600121553	x1
4,50	47 80	D2409D0450	3336600121584	x1
4,80	52 86	D2409D0480	3336600121614	x1
5	52 86	D2409D0500	3336600121638	x1
5,20	52 86	D2409D0520	3336600121652	x1
5,50	57 93	D2409D0550	3336600121683	x1
6	57 93	D2409D0600	3336600121737	x1
6,50	63 101	D2409D0650	3336600121782	x1
7	69 109	D2409D0700	3336600121836	x1
7,50	69 109	D2409D0750	3336600121881	x1
8	75 117	D2409D0800	3336600121935	x1
9	81 125	D2409D0900	3336600122031	x1

Ø	WL TL	ref.	EAN	packaging*
9,50	81 125	D2409D0950	3336600122086	x1
10	87 133	D2409D1000	3336600122130	x1
10,50	87 133	D2409D1050	3336600122154	x1
11	94 142	D2409D1100	3336600122161	x1
11,50	94 142	D2409D1150	3336600122185	x1
12	101 151	D2409D1200	3336600122192	x1
12,50	101 151	D2409D1250	3336600122215	x1
13	101 151	D2409D1300	3336600122222	x1
13,50	108 160	D2409D1350	3336600122239	x1
14	108 160	D2409D1400	3336600122246	x1
15	114 169	D2409D1500	3336600122260	x1
15,50	120 178	D2409D1550	3336600122277	x1
16,50	125 184	D2409D1650	3336600122291	x1
17	125 184	D2409D1700	3336600122307	x1
17,50	130 191	D2409D1750	3336600122314	x1
18	130 191	D2409D1800	3336600122321	x1
18,50	135 198	D2409D1850	3336600122338	x1
19	135 198	D2409D1900	3336600122345	x1
19,50	140 205	D2409D1950	3336600122352	x1
20	140 205	D2409D2000	3336600122369	x1

702
DIN 338

HSS with multi-layers coating



NEW



Features
Angle point 130°,
Helix type "S" with
multi-layers coating

Benefits
The multi-layers reacts
as a thermic barrier,
Better extraction of shavings,
hardness 3000 HV,
Better penetration in
the hard steels

Materials
Stainless steel,
Steel,
Zamac,
Bronze,
Graphite

Available
in june 2010

Ø	WL TL	ref.	EAN	packaging*
1,0	12 34	702D01	3336600154773	1=2
1,5	18 40	702D01,5	3336600154780	1=2
2,0	24 49	702D02	3336600154797	1=2
2,5	30 57	702D02,5	3336600154803	1=2
3,0	33 61	702D03	3336600154810	1=2
3,2	36 65	702D03,2	3336600154827	1=2
3,5	39 70	702D03,5	3336600154834	1=2
4,0	43 75	702D04	3336600154841	1=2
4,2	43 75	702D04,2	3336600154858	1=2
4,5	47 80	702D04,5	3336600154865	1=2
4,8	47 80	702D04,8	3336600154872	1=2
5,0	52 86	702D05	3336600154889	1=2
5,2	52 86	702D05,2	3336600154896	x1
5,5	57 93	702D05,5	3336600154902	x1
6,0	57 93	702D06	3336600154919	x1
6,2	57 93	702D06,2	3336600154926	x1

Ø	WL TL	ref.	EAN	packaging*
6,5	63 101	702D06,5	3336600154933	x1
6,8	69 109	702D06,8	3336600154940	x1
7,0	69 109	702D07	3336600154957	x1
7,5	69 109	702D07,5	3336600154964	x1
8,0	75 117	702D08	3336600154971	x1
8,5	75 117	702D08,5	3336600154988	x1
9,0	81 125	702D09	3336600154995	x1
9,5	81 125	702D09,5	3336600155008	x1
10,0	87 133	702D10	3336600155015	x1
10,5	87 133	702D10,5	3336600155022	x1
11,0	94 142	702D11	3336600155039	x1
11,5	94 142	702D11,5	3336600155046	x1
12,0	101 151	702D12	3336600155053	x1
12,5	101 151	702D12,5	3336600155060	x1
13,0	101 151	702D13	3336600155077	x1

*Packaging : TUBE (page 50)